



Windows 11

12.2" Tablet

## Key features

- ◆ IP65, MIL-STD-810H
- ◆ 3G/4G/5G, WiFi 2.4 GHz + 5GHz, Bluetooth 4.2 (BLE), GPS
- ◆ NFC, 1D/2D Barcode scanner
- ◆ The support of the international VESA desktop style, hanging wall style installation
- ◆ Capacitive multi-touch supports glove touch, water rejection
- ◆ Battery built-in 7.4V /860mAh and battery hot swappable 7.4V/6300mAh



## OS

---

- ◆ Windows® 11 PRO / 11 IOT

## CPU

---

- ◆ Intel Celeron N150 / Core i7-855U / Core i5-1235U / Core i7-1235U

## Memory

---

- ◆ 8 GB or 16 GB DDR4L as lcore i7 option)
- ◆ 128 GB SSD / 256GB / 512GB SSD

## Display

---

- ◆ 12.2" 1920 x 1200px IPS
- ◆ 10 points capacitive, G+G
- ◆ 650 nits

## RF

---

- ◆ 4GLTE B1/B3/B7/B8/B20/B28A
- ◆ 5G N1/N3/N5/N7/N8/N20/N28/N38/N40/N41/N71/N77/N78/N79A (optional)
- ◆ WiFi 802.11 a/b/g/n/ac (2.4GHz & 5GHz)
- ◆ Bluetooth 4.2 (BLE) distance 10m
- ◆ GNSS ublox (GLONASS,GPS,Beidou)

## Camera

---

- ◆ 2MP front camera
- ◆ 8MP rear camera with flash light

## Control Button

---

- ◆ Power ON/OFF
- ◆ Volume + / -
- ◆ Scanning
- ◆ Home

## Sensor & Data Collection

---

- ◆ RFID NXP100 (optional)
- ◆ 1D barcode reader Honeywell N6551 (optional)
- ◆ 2D barcode reader Honeywell N3680 (optional)
- ◆ Gyroscope, E-compass, G-Sensor

## Power Adapter

---

- ◆ AC100V - 240V, output DC 19V3.42A/65W
- ◆ 5.5 mm DC jack

## Batteries

---

- ◆ Lithium Polymer 7,4V - 6300 mA hot swappable
- ◆ Lithium Polymer 7,4V - 860 mA built-in

## Audio

---

- ◆ 3.5 mm Audio jack Speaker / Microphone

## I/O Interface

---

- ◆ USB Type Cx1
- ◆ USB 3.0 x1
- ◆ SIM card x1
- ◆ TF card (max 128G) x1
- ◆ HDMI 1.4a x1
- ◆ 12 pins Pogo Pin x1

## Module Extension (5 choose 1)

- ◆ Serial port DB9 (Rs232) x1
- ◆ Ethernet RJ45 10/100 x1
- ◆ USB 2.0 x1
- ◆ 1D barcode reader
- ◆ 2D barcode reader

## Dimensions and Weight

---

- ◆ 339 x 230 x 26 mm
- ◆ 1.995 kg

## Durability

---

- ◆ IP65
- ◆ Shock & Vibration
- ◆ Drop 1,2m
- ◆ MIL-STD-810G

## Environmental

---

- ◆ Operating temperature: -20°C to 60°C
- ◆ Storage temperature: -30°C to 70°C
- ◆ Humidity: 0% - 95%

## Warranty

---

- ◆ «Continuité» warranty extension total 3 years (return workshops, repair within 10 working days upon receipt of the material - without breakages)
- ◆ «Confort» Contract 3 years, full service contract (return workshops, repair within 5 working days upon receipt of the material - with breakages)

# Product Six Views



\* All technical data, specification and performance figures subject to change without notice.



**Harness carrying case**  
AT-CART11007



**Battery 6300 mA 7.4V**  
AT-CART12003



**Shoulder strap**  
AT-CAE1207



**Carry handle**  
AT-CART12003



**Hand strap**  
AT-CART12006



**4 Slots batteries charger**  
AT-CART1208



**Cigarette light adapter**  
AT-CART12212



**Destock Dock**  
AT-CART12001



**Vehicle Dock**  
AT-CART12005