



CHECK BOX

Welcome @ CheckBox - the New generation FDM 2.0

Meeting the Belgian GKS 2.0 requirements

Tailored made for the hospitality software developers & the resellers

Start the easy implementation today

Register - Download SDK & Tools - Connect to your Software - Get support & documentation



LAN / WiFi 2.4GHz
as a standard communication



Cloud based solution



3 years warranty



Easy to install in the field



Developed and assembled
in Belgium



Free of charge SDK Software



100% compliant with GKS 2.0
nothing more, nothing less



Personal contact & support
(competence, time efficiency, reliability)



www.checkbox.be

CheckBox FDM 2.0

Welcome @ CheckBox - the New generation FDM 2.0

Meeting the Belgian GKS 2.0 requirements

Tailored made for the hospitality software developers & the resellers

Start the easy implementation today

Register - Download SDK & Tools - Connect to your Software - Get support & documentation

Physical Characteristics	
Weight	120 grams
Dimensions	120 mm x 80 mm x 25 mm
Power Specifications	
Power Consumption	5 Watts
Power Connector	USB-C (5VDC, 1A, power only)
LAN Ethernet Connection	Speed 100/100 Mbps - RJ45 Connector
Wi-Fi Connectivity	
Standards	IEEE 802.11 b/g/n
Frequency	2.4 GHz
Speed	Up to 150 Mbps (depending on signal strength and network conditions)
USB-C Power Connector	Power Only - 5VDC, 1A
Memory and Storage	4GB internal storage for buffering and data storage
Environmental Specifications	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	5% to 95% non-condensing



Avenue Zénobe Gramme 29
1300 - Wavre



[+3210394900](tel:+3210394900)



info@eutronix.be

